

# Architect W500B

## PRODUCT SPECIFICATION SHEET

---



The 2nd generation of Architect high-power static-beam lasers (sometimes called sky lasers or landmark lasers) is our reaction to globally increasing demand for super bright lasers. These are great for highlighting significant landmarks, structures and buildings.

The beam coming out of the Architect systems draws attention from many miles away. It adds a great deal of sublimity to already majestic nature-made, or human-made objects, making them even more unique, appealing and desirable.

The optional DMX-controlled heavy-duty platform offers a 350-degree pan and 126-degree tilt of the whole Architect fixture, allowing the beam to be moved and scanned across the sky.

# Architect W500B

## PRODUCT SPECIFICATION SHEET



### SPECIFICATIONS

<b>Source   IP-rating   Type:</b>	Semiconductor laser diode   IP65   Full-colour RGB sky laser
<b>Suitability:</b>	Architectural installations   Landmark and Sky illumination
<b>System control:</b>	FB4 [ArtNet, DMX] / Manual via supplied remote control box   Dimming 100-0%
<b>Compliant with:</b>	EN 60825-1
<b>Weight [kg]:</b>	80 [laser projector] 46 [chiller]
<b>Size [WxHxD, mm]:</b>	640 x 574 x 682 [laser projector] 686 x 399 x 483 [chiller]
<b>Guaranteed opt. output:</b>	486 watts
<b>Installed modules R   G   B [W]:</b>	152   188   146
<b>Wavelengths [nm, ±5nm]:</b>	637   525   465
<b>Beam size [mm]:</b>	400 x 400
<b>Beam divergence [mrad]:</b>	3.4 [full angle, averaged value]
<b>X-Y scanners:</b>	Single beam output   Pan & tilt possible with the optional DMX platform
<b>Power requirements [V]   Input:</b>	100-240/50-60Hz   Neutrik powerCON TRUE1 [laser projector] 200-230/50-60Hz [chiller]
<b>Max. power consumption [VA]:</b>	< 2,000 W [laser projector] < 1,600 W [chiller]
<b>Operation temperature [°C]:</b>	5-40 [full power output at 5-35]
<b>Included in the set:</b>	Chiller, 10M Water supply hoses, 2x Heavy-duty flight case, 10M AC power cable, 10M Control signal cable, 0-5 Volt RGB controller, E-STOP Remote with 10M 3-pin XLR cable, Set of 2 safety keys, USB memory stick with the user manual, QC certificate.
<b>HW features:</b>	-
<b>Laser safety features:</b>	Emission warning beacon, emission delay, magnetic interlock, electronic shutter, Emergency STOP system with keyed remote and manual RESTART button.
<b>note A:</b>	-
<b>note B:</b>	-
<b>Luminous flux [lm]:</b>	130,200
<b>Coolant:</b>	Water + 15% glycol, 6-10 l/min, 20°C
<b>Hose fittings:</b>	CEJN series 567